



Comparison against general plywood

SP101 Flooring Plywood®

Specification characteristics	SP101 Flooring Plywood®	General commercial plywood
Veneer Glue bond	EN 314 Class 3 Exterior fully tested and reliable	Supposedly EN314 Class 2 minimum, but not always tested. Glue lines are known to consistently fail in flooring applications
Moisture content	Very accurate and precise drying in manufacture resulting in a fully stable and conditioned panel	In some panels can vary a lot resulting in distortion. Poor drying can cause mould growth on the surface of boards
Thickness of face and back veneers	Minimum 0.75mm for maximum performance. Works well with all glues and resins and has been tested and approved by most manufacturers	Can be as low as 0.12mm and are readily permeable to moisture and glue. These thin veneers also telegraph the inferior core quality onto the faces
Core veneer quality	No core overlap or gaps therefore creating a high quality surface finish	Core overlaps and gaps are common in most plywoods and result in poor surface quality and thickness variation
Flatness and stability	Superior construction makes SP101® much more reliable and stable	Boards can be badly distorted due to manufacturing processes
Thickness and dimensional tolerances	Very tightly controlled to ensure optimum performance	Can vary considerably in some panels creating further surface preparation attention
Ease of working	Can be worked easily, and will usually cut with a fitter's knife	Can be difficult to work and may be unstable
TFT Woodexperts Diamond Mark Certified	Every technical detail is tested and certified by TFT Woodexperts to guarantee performance	Most panels are not third party tested as this can add too much cost to general commercial panels
CFA Guidance Note Compliant	SP101® is manufactured in accordance with this note	Most panels will not comply with the note and are not manufactured with any regard to it
Floor Fitting Training Schools	Most UK training schools use SP101® in their classes in order to promote best practice to students	Training schools are reluctant to use any panels that do not meet industry requirements and are not guaranteed fit for purpose

To find out more you can visit SP101.CO.UK

FSC stock available.

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@plywood.co.uk
www: www.hanson-plywood.co.uk

