

SP101 Flooring Plywood®

Plywood for flooring applications, fit for purpose and quality guaranteed.

Problems with gluing failure, varying dimensions, flatness, poor surface quality?

SP101 Flooring Plywood® is developed specifically for the purpose of flooring underlay and is fully tested and approved to the necessary industry standards and requirements.

The flooring trade recognises the need to use plywood that has been produced to a defined industry specification and as such is guaranteed fit for purpose.

After extensive consultation with expert bodies, the CFA has produced a comprehensive guidance note on plywood which is now in general circulation.

This guidance note is intended to help the industry in specifying and using panels that are entirely suitable as a component of the high value finished floor.

SP101 is the only Panel Product to achieve Diamond Mark Certification.



Specification detail

TFT Diamond Mark	Certified
Manufactured to	EN 636-2
Appearance class	Based on class 1 from EN 635-2
Glue bond	EN 314-2 class 3 (exterior) LFE E1 emission
Wood species	Mixed hardwood
Moisture content	8-10%
Thickness tolerance	3.6mm & 5.5mm: ±0.2mm, 9mm: ±0.3mm
Dimensional square tolerance	Tight to EN 315
Veneers	Overlay quality without core overlap and gaps
Thicker outer veneers	Minimum 0.75mm
Average density	Approx 500 kg/m ³
European Timber Regulation (EUTR) status	Compliant
CE Marked	BS EN 13986

To find out more you can visit SP101.CO.UK

FSC® stock available.



Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL
Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk

