



Plywood specifically designed for subfloor preparation

Guaranteed fit-for-purpose and quality assured.

SP101 Flooring Plywood® is developed specifically for the purpose of flooring underlay and is fully tested and approved to the necessary industry standards and requirements.

CFA Guidance on plywood specification has now been recognised by the British Standards Institution and has been incorporated as a normative annex into **BS 8203 - Code of practice for the installation of resilient floor coverings**.

This normative annex is intended to help the industry in specifying and using panels that are entirely suitable as a component of the high value finished floor.

SP101 Flooring Plywood® is the first plywood panel to be manufactured in accordance, and certified as fully compliant, with **BS 8203**.

SPECIFICATION DETAIL:

TFT Diamond Mark	Certified
Manufactured to	BS 8203:2017 EN 636-2
Appearance class	Based on Class 1 from EN 635-2
Glue bond	EN 314-2 Class 3 (exterior) LFE E1 emission
Wood species	Mixed tropical hardwood
Moisture content	8-10%
Thickness tolerance	5.5mm: ±0.2mm, 9mm: ±0.3mm
Dimensional square tolerance	Tight to EN 315
Veneers	Overlay quality without core overlap and gaps
Thicker outer veneers	Minimum 0.75mm
Average density	Approx 500 kg/m ³
European Timber Regulation (EUTR) status	FLEGT Licensed (Verified Legally compliant)
CE Marked	BS EN 13986
FSC® Stock	Available

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444

Fax: 01422 330706

Email: sales@hanson-plywood.co.uk

www.hanson-plywood.co.uk



July 2019