



## Plywood specifically designed for subfloor preparation

Guaranteed fit-for-purpose and quality assured.

SP101 Flooring Plywood® is developed specifically for the purpose of flooring underlay and is fully tested and approved to the necessary industry standards and requirements.

CFA Guidance on plywood specification has now been recognised by the British Standards Institution and has been incorporated as a normative annex into **BS 8203 - Code of practice for the installation of resilient floor coverings**.

This normative annex is intended to help the industry in specifying and using panels that are entirely suitable as a component of the high value finished floor.

SP101 Flooring Plywood® is the first plywood panel to be manufactured in accordance, and certified as fully compliant, with **BS 8203**.

### SPECIFICATION DETAIL:

|  |  |
|--|--|
| TFT Diamond Mark                         | Certified                                      |
| Manufactured to                          | BS 8203:2017<br>EN 636-2                       |
| Appearance class                         | Based on Class 1 from EN 635-2                 |
| Glue bond                                | EN 314-2 Class 3 (exterior)<br>LFE E1 emission |
| Wood species                             | Mixed tropical hardwood                        |
| Moisture content                         | 8-10% at manufacture                           |
| Thickness tolerance                      | 5.5mm: ±0.2mm,<br>9mm: ±0.3mm                  |
| Dimensional square tolerance             | Tight to EN 315                                |
| Veneers                                  | Overlay quality without core overlap and gaps  |
| Thicker outer veneers                    | Minimum 0.75mm                                 |
| Average density                          | Approx 500 kg/m <sup>3</sup>                   |
| European Timber Regulation (EUTR) status | FLEGT Licensed<br>(Verified Legally compliant) |
| CE Marked                                | BS EN 13986                                    |
| FSC® Stock                               | Available                                      |

#### CONTACT:

Drakes Industrial Estate  
Shay Lane, Halifax  
West Yorkshire  
HX3 6RL

Tel: 01422 330444

Fax: 01422 330706

Email: [sales@hanson-plywood.co.uk](mailto:sales@hanson-plywood.co.uk)

[www.hanson-plywood.co.uk](http://www.hanson-plywood.co.uk)



October 2020